

Rittal – The System.

Faster – better – everywhere.

► Roof-mounted fan, roof vent – SK 3149.007

Date : Jan 22, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Roof-mounted fan, roof vent – SK 3149.007

created: 22.01.2020 build on www.rittal.com/il-en



Discontinued article.

This item will be discontinued on: 30.04.2017 |||This item is being replaced by: 3139100

Product description

Design:	Unit ready for connection with built-in radial fan
Material:	Sheet steel, spray-finished
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 43
Supply includes:	Sealing and assembly parts Drilling template Connection cable (3 m)
Product modification:	Mounting cut-outs are not compatible. If reusing the roof plate, adaptor frame 5050.700 is required.
Note:	Via additional installation of the filter holder with filter mat, a protection category of IP 44 is achieved with roof vent 3148.007

Product features

Air throughput (unimpeded air flow):	360 m ³ /h
---	-----------------------

Air throughput, unimpeded air flow (without filter mats):	
--	--

Air throughput,	
------------------------	--

**unimpeded air flow
(with filter mats):**

Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 420 mm Height: 95 mm Depth: 340 mm
Required mounting cut-out:	Width: 345 mm Depth: 265 mm
Temperature range:	Operation (environment): -10 °C...+60 °C
Power consumption P_{el}:	At 50 Hz: 42 W
Rated current max.:	At 50 Hz: 0.2 A
Noise level:	At 50 Hz: 53 dB(A)
Packs of:	1 pc(s).
Weight/pack:	7.8 kg
EAN:	4028177165342
Customs tariff number:	84145915
ETIM 7.0:	EC000320
ETIM 6.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 6.0/6.1:	27180716
Product description:	SK Roof-mounted fan, 360 m³/h, 230 V, 1~, 50/60 Hz, WHD: 420x95x340 mm
Approvals	
Approvals:	Approval overview
Certificates:	EAC
Declarations:	Declaration of conformity Manufacturer's declaration