

## **ECO SERIES VACUUM PUMPS**



- Designed specifically for HVAC/R Service
- Two stage rotary vane pump design
- Compact design with aluminium housing and easy to grip carrying handle
- Very quiet operation
- High pumping capacity reduces evacuation time
- Carrying handle stays cool to the touch
- Easy to start
- Both 1/4" and 3/8" SAE flare inlet connections allow for flexibility of connections
- Vacuum pump oil included
- Value priced but still manufactured to the highest quality and performance specifications

Technical Data	ECO-3	ECO-5	ECO-5-DV	ECO-5-R32	ECO-9
Voltage:	230 V / 50/60 Hz	230 V / 50/60 Hz	110V-220V / 50 - 60 Hz	230 V / 50/60 Hz	230 V / 50/60 Hz
Free Air Displace- ment:	70 l/min (2.5 CFM) 84 l/min (3.0 CFM)	142 l/min (5 CFM)	142 l/min (5 CFM)	142 l/min (5 CFM)	255 l/min (9 CFM)
Ultimate vacuum:	15 microns	15 microns	15 microns	15 microns	15 microns
Motor:	0.25 kW	0.37 kW	0.37 kW	0.37 kW	0.74 kW
Intake Fitting:	1/4" / 3/8" flare	1/4 SAE & 3/8" SAE	1/4 SAE & 3/8" SAE	1/4" SAE & 3/8" SAE	1/4" SAE & 3/8" SAE
Oil capacity:	250 ml	325 ml	325 ml	325 ml	590 ml
Dimensions (mm):	315 x 124 x 240 mm	335 x 140 x 250 mm	335 x 140 x 250 mm	335 x 140 x 250 mm	406 x 152 x 279 mm
Net weight (kg)	8.6 kg	10.4 kg	10.4 kg	10.4 kg	16.8 kg
Part No.	4687343	4686913	4682692	4687805	4688089