



02236831

SKR 240/16

Where to buy 🛛

Product specifications

Characteristic	Value
Case	E15
Chip Technology	Standard recovery
Current (A)	240 A
Dimensions (LLxBBxHH) mm	190SW32M16
Features	 Reverse voltages up to 1800 V Hermetic metal case with glass insulator Threaded stud ISO M16 x 1,5 SKN / SKR 240/04 /16 also available with threaded stud 3/4-16UNF (e.g. SKR240/12UNF) SKR: cathode to stud
Housing	Stud Screw Fit
Part Number	02236831
Product Line	Stud Screw Fit
Product Status	In production
Product Type	SKR 240/16
Surge Current (A)	6000 A
Technology	Diodes
Typical Applications	 All-purpose mean power rectifier diodes Cooling via heatsinks Non-controllable and half-controllable rectifiers Free-wheeling diodes Recommended snubber network: Rc: 0,5µf, 30 ω (pr = 2w), rp = 50 kω (pr = 20 W)
Voltage (V)	1600 V

For the most current information and other product assets, please use this link to visit the product page on Semikron Danfoss 🛙

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.