



IFL 15-30L-11TP-1766

- Metal enclosure
- DC 4-wire
- Long design
- Design M30

Data

Ordering data

Product type description	IFL 15-30L-11TP-1766
Article number (order number)	101127027
EAN (European Article Number)	4030661278285
eCl@ss number, version 12.0	27-27-40-01
eCl@ss number, version 11.0	27-27-01-01
eCl@ss number, version 9.0	27-27-01-01
ETIM number, version 7.0	EC002714
ETIM number, version 6.0	EC002714

Approvals - Standards

Certificates	CCC
--------------	-----

General data

Standards	DIN VDE 0660-208 EN IEC 60947-5-2
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush

Housing material	Brass
Housing coating material	nickel-plated
Active area	Plastic
Material of the nuts	Brass
Gross weight	180 g

General data - Features

Cable sleeve	Yes
Number of cable wires	4

Mechanical data

Tightening torque of nuts, maximum	30 Nm
------------------------------------	-------

Mechanical data - Switching distances according EN IEC 60947-5-3

Nominal switching distance S_n	15 mm
----------------------------------	-------

Mechanical data - Connection technique

Length of cable	2 m
Termination	Cable
Wire cross-section	0.25 mm ²
Material of the Cable mantle	Thermoflex

Mechanical data - Dimensions

ISO thread of the sensor	M30
width across flats	36 BK
Length of sensor	100 mm

Ambient conditions

Degree of protection	IP67
----------------------	------

Ambient temperature +0 ... +110 °C

Protection class 0

Electrical data

No-load supply current I_0 , typical	5.5 mA
Rated operating voltage	10 ... 60 VDC
Operating current	200 mA
Switching element	NO contact and NC contact (antivalent)
Protection circuit integrated	inductive interference protection Protection against polarity reversal
Switching frequency, approx.	50 Hz
Type of voltage range	DC

Electrical data - Digital Output

Voltage drop U_d , maximum	1 V
Current at Voltage drop U_d	0.2 A
Design of control elements	p-type

Note

Note (General) Instead of nuts, a mounting clamp can be provided.

Ordering code

Product type description:
IFL (1)-(2)(3)-(4)(5)(6)(7)-(8)

(1)

10 Switching distance 10 mm

15 Switching distance 15 mm

(2)

30 Cylinder, thread M30, metal

300 Cylinder, thread M30, plastic

(3)

without	Standard body
M	Miniature body
L	Long design

(4)

01	Opener (NC)
10	Normally open contact (NO)
10/01	NO contact / NC contact with wiring compartment
11	1 NO contact / 1 NC contact antivalent

(5)

without	Cable
ST	Male connector
T	Conductor with strain relief
D	DC 2-wire

(6)

without	Standard connector version
2	Alternative connector version

(7)

N	n-type
P	p-type

(8)

1310	Can be used up to +110 C (for alternating current (AC) only)
2130	Can be used up to +130 C, without LED switching conditions display
1766	Can be used up to +110 C (for p-type or n-type only)

Pictures

Product picture (catalogue individual photo)




ID: kifl1f51

| 421,7 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 px - 72 dpi

| 40,1 kB | .png | 74.083 x 111.125 mm - 210 x 315 px - 72 dpi

| 26,4 kB | .jpg | 82.197 x 123.472 mm - 233 x 350 px - 72 dpi

Dimensional drawing basic component




ID: lifl1g36

| 26,1 kB | .cdr |

| 6,8 kB | .png | 74.083 x 51.153 mm - 210 x 145 px - 72 dpi

| 93,9 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 px - 72 dpi

Diagram



ID: id4lk13

| 35,2 kB | .cdr |

| 60,7 kB | .jpg | 352.778 x 146.756 mm - 1000 x 416 px - 72 dpi

| 2,8 kB | .png | 74.083 x 30.692 mm - 210 x 87 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 21/02/2024, 09:32