

Measuring electric fields from 300 MHz to 50 GHz

using instruments in the NBM-500 family

- ▲ **Field exposure from satellite communications and radar in the occupational environment, leak detection**
- ▲ **Isotropic (non-directional) measurement**
- ▲ **True RMS indication even with multiple, superimposed, strong pulsed signals**

The probe contains three orthogonally-arranged thermocouple sensors. Each sensor consists of several thermocouples, which together form a dipole. The output voltage from the thermocouple is proportional to the coupled power level, regardless of the signal shape. The isotropic measurement value is obtained by addition within the probe.

APPLICATIONS

The probe detects electric fields from 300 MHz to 50 GHz, covering the fields found in satellite communications and radar equipment. The use of thermocouples naturally results in a true RMS reading, making the probe particularly suitable for measuring human safety limit values in a multi-frequency environment.

PROPERTIES

The probe is mechanically and electrically robust. The probe head is made of foam material to provide effective protection for the sensors, while having excellent RF characteristics. The sensors can handle high impulse power levels.

CALIBRATION

The probe is calibrated at several frequencies. The correction values are stored in an EPROM in the probe and are automatically taken into account by the NBM instrument. Calibrated accuracy is thus obtained regardless of the combination of probe and instrument.



SPECIFICATIONS ^a

Probe EF5091		Electric (E-)Field	
Frequency range ^(b)	300 MHz to 50 GHz		
Type of frequency response	Flat		
Measurement range	8 to 614 V/m	17 μ W/cm ² to 100 mW/cm ²	
Dynamic range	37 dB		
CW damage level	1500 V/m	0.6 W/cm ²	
Peak damage level ^(c)	27 kV/m	200 W/cm ²	
Sensor type	Thermocouple (inherent True RMS detection)		
Directivity	Isotropic (Tri-axial)		
Readout mode / spatial assessment	Combined 3-axis (RSS)		
UNCERTAINTY			
Flatness of frequency response ^(d) Calibration uncertainty not included	± 1.25 dB (1.8 GHz to 40 GHz)		
Calibration uncertainty ^(e) @ 1 mW/cm ² (61.4 V/m)	± 1.5 dB (300 MHz to 1.2 GHz) ± 1.3 dB (≥ 1.2 GHz to 45.5 GHz)		
Linearity Referred to 1 mW/cm ² (61.4 V/m)	± 1 dB (24 to 61.4 V/m)	± 1 dB (0.15 to 1 mW/cm ²)	
Isotropic response ^(f)	± 0.3 dB (> 61.4 V/m)		
Temperature response ^(g)	± 1 dB		
Temperature response ^(g)	± 0 dB		
GENERAL SPECIFICATIONS			
Calibration frequencies	0.3/ 0.75/ 1.8/ 2.45/ 4/ 5/ 6/ 8.2/ 9.3/ 10/ 11/ 18/ 26.5/ 40/ 45.5 GHz		
Recommended calibration interval	24 months		
Temperature range			
Operating	0 °C to +50 °C		
Non-operating (transport)	-40 °C to +70 °C		
Humidity	5 to 95 % RH @ ≤ 25 °C	≤ 23 g/m ³ absolute humidity	
Size	318 mm x 66 mm \varnothing		
Weight	90 g		
Compatibility	NBM-500 series meters		
Country of origin	Germany		

(a) Unless otherwise noted specifications apply at reference condition: device in far-field of source, ambient temperature 23 \pm 3 °C, relative air humidity 40% to 60%, sinusoidal signal

(b) Cutoff frequency at approx. -3 dB

(c) Within any interval of 10ms an average value of 0.6 W/cm² and a peak value of 200 W/cm² should not be exceeded

(d) Frequency response can be compensated for by the use of correction factors stored in the probe memory

(e) Accuracy of the fields generated to calibrate the probes

(f) Uncertainty due to varying polarization (verified by type approval test for meter with probe). Ellipse ratio included and calibrated for each probe

(g) The conversion factor of thermocouple sensors is inherently not dependent on environmental temperature

ORDERING INFORMATION

	Part number
Probe EF5091, E-field for NBM, thermocouple, 300 MHz – 50 GHz, isotropic	2402/03D
Probe EF5091, E-field, ACC - with accredited (DAkkS) calibration up to 18 GHz, basic unit required	2402/03D/ACC