

Switch - FL SWITCH SFNB 5TX - 2891001

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ethernet switch, 5 TP RJ45 ports, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function


Product Features

- ✓ Multi-mode and single-mode fiberglass connections are available for larger distances
- ✓ Auto negotiation and autocrossing detection simplifies installation and setup
- ✓ Security options with cable locking
- ✓ Local diagnostic indicators with LEDs
- ✓ RJ45 ports support a transmission speed of 10/100 Mbps; fiber optic ports support 100 Mbps



Ethernet

Key commercial data

| | |
|------------------------|---|
| Packing unit | 1 PCE |
| Minimum order quantity | 10000 PCE |
| GTIN |  4 046356 457163 |
| Custom tariff number | 85176200 |
| Country of origin | TAIWAN |

Technical data

Interfaces

| | |
|---------------------------|-----------------------------------|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 5 (RJ45 ports) |
| Connection method | RJ45 |
| Note on connection method | Auto negotiation and autocrossing |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission speed | 10/100 MBit/s |

Function

Switch - FL SWITCH SFNB 5TX - 2891001

Technical data

Function

| | |
|----------------------------------|--|
| Basic functions | Unmanaged switch / autonegotiation, complies with IEEE 802.3, store and forward switching mode |
| Status and diagnostic indicators | LEDs: U _s , link and activity per port |

Network expansion parameters

| | |
|--|--|
| Cascading depth | Network, linear, and star structure: any |
| Maximum conductor length ((twisted pair) | 100 m |

Supply voltage

| | |
|-----------------------------|--|
| Supply voltage | 24 V DC |
| Residual ripple | 3.6 V _{pp} (within the permitted voltage range) |
| Supply voltage range | 12 V DC ... 48 V DC |
| Typical current consumption | 185 mA (@24 V DC) |
| Max. current consumption | 345 mA (@12 V C) |

General data

| | |
|--|--|
| Width | 28 mm |
| Height | 110 mm |
| Depth | 70 mm |
| Mounting type | DIN rail |
| Type AX | Block design |
| Weight | 205 g |
| Degree of protection | IP20 |
| Ambient temperature (operation) | -10 °C ... 60 °C |
| Ambient temperature (storage/transport) | -20 °C ... 85 °C |
| Permissible humidity (operation) | 5 % ... 95 % (no condensation) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (no condensation) |
| Air pressure (operation) | 86 kPa ... 108 kPa (up to 1500 m above mean sea level) |
| Air pressure (storage/transport) | 66 kPa ... 108 kPa (up to 3500 m above mean sea level) |
| Housing material | Aluminum |
| Noise emission | EN 61000-6-4 |
| Noise immunity | EN 61000-6-2 |

Conformity with EMC directives

| | |
|---------------------------------|---|
| Developed in acc. with standard | IEC 61000-6.2 |
| Test standard | IEC 61000-4-2 (ESD) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-3 (immunity to radiated interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-4 (burst) |

Switch - FL SWITCH SFNB 5TX - 2891001

Technical data

Conformity with EMC directives

| | |
|---------------|--|
| Test result | Criterion B |
| Test standard | IEC 61000-4-5 (surge) |
| Test result | Criterion B |
| Test standard | IEC 61000-4-6 (immunity to conducted interference) |
| Test result | Criterion A |
| Test standard | IEC 61000-4-8 (immunity to magnetic fields) |
| Test result | Criterion A |
| Test standard | EN 55022 (emitted interference) |
| Test result | Criterion A |

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000734 |
| ETIM 3.0 | EC000734 |
| ETIM 4.0 | EC000734 |
| ETIM 5.0 | EC000734 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43201410 |
| UNSPSC 13.2 | 43201410 |
| UNSPSC 6.01 | 43172901 |
| UNSPSC 7.0901 | 43201404 |

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27250501 |
| eCl@ss 4.1 | 27250501 |
| eCl@ss 5.0 | 19030117 |
| eCl@ss 5.1 | 19030117 |
| eCl@ss 6.0 | 19170106 |
| eCl@ss 7.0 | 19170106 |

Approvals

Approvals

Switch - FL SWITCH SFNB 5TX - 2891001

Approvals

Approvals


UL Recognized / cUL Recognized / cULus Recognized


Ex Approvals

UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 

Accessories

Accessories

Assembly

End clamp - E/NS 35 N - 0800886



End clamp, width: 9.5 mm, color: gray

Cable/conductor

Switch - FL SWITCH SFNB 5TX - 2891001

Accessories

Patch cable - FL CAT5 PATCH 0,3 - 2832250



Patch cable, CAT5, assembled, 0.3 m

Patch cable - FL CAT5 PATCH 0,5 - 2832263



Patch cable, CAT5, assembled, 0.5 m

Patch cable - FL CAT5 PATCH 1,0 - 2832276



Patch cable, CAT5, assembled, 1.0 m

Patch cable - FL CAT5 PATCH 1,5 - 2832221



Patch cable, CAT5, assembled, 1.5 m

Patch cable - FL CAT5 PATCH 2,0 - 2832289



Patch cable, CAT5, assembled, 2.0 m

Switch - FL SWITCH SFNB 5TX - 2891001

Accessories

Patch cable - FL CAT5 PATCH 3,0 - 2832292



Patch cable, CAT5, assembled, 3.0 m

Patch cable - FL CAT5 PATCH 5,0 - 2832580



Patch cable, CAT5, assembled, 5.0 m

Patch cable - FL CAT5 PATCH 7,5 - 2832616



Patch cable, CAT5, assembled, 7.5 m

Patch cable - FL CAT5 PATCH 10,0 - 2832629



Patch cable, CAT5, assembled, 10.0 m

Dust protection - FL RJ45 PROTECT CAP - 2832991



Dust protection caps for RJ45 female connector
