

Hydrostats, pressure and vacuum pressure switches up to 10 bar



- Elements in contact with fluid are in stainless steel, laser welded.
- SPDT contact rating 250Vac 16(6)A.



CODE	RANGE bar	DIFFERENTIAL* bar	SENSITIVE ELEMENT MAX. PRESSURE BAR	CONNECTION G 1/4	PROTECTION DEGREE
B11AN	0,15 ÷ 1	0,1 fixed	20	female	IP40
B11AN4	0,15 ÷ 1	0,1 fixed	20	male	IP40
B11ANY	0,15 ÷ 1	0,1 fixed	20	female	IP65
B11AN4Y	0,15 ÷ 1	0,1 fixed	20	male	IP65
B12AN	-0,82 ÷ 0	0,1 fixed	2,5	female	IP40
B12AN4	-0,82 ÷ 0	0,1 fixed	2,5	male	IP40
B12BN	0,2 ÷ 2	0,1 ÷ 0,5	4	female	IP40
B12ANY	-0,82 ÷ 0	0,1 fixed	2,5	female	IP65
B12BNY	0,2 ÷ 2	0,1 ÷ 0,5	4	female	IP65
303298LA	G1/2 cable gland in V0 self-extinguishing, shockproof thermoplastic material				
2593367	Protection casing IP44				

* The differential is to be deducted from the set value.

