



## Electronically level-controlled drain BEKOMAT 12 CO PN63

Robust, favourably priced condensate drain for oil-free, aggressive condensate from compressor stations with an intake capacity up to 6.5 m<sup>3</sup> / min.

**Application:** oil-contaminated and oil free, aggressive condensate

### Characteristics

- Reliable condensate drain without unnecessary loss of compressed air
- Simple installation
- No preventive checks or maintenance required
- Clear and distinct display of operating parameters by LED Display
- Self-monitoring thanks to integrated alarm system
- Non-wearing, capacitive measuring system without moving parts
- Rugged and durable construction
- Potential-free alarm contact
- Test button for checking device functions

Housing made of die-cast aluminium resistant to corrosion, complete with glass-bead finishing. High-grade protection is provided internally and externally by a hard coat.

Problems in the condensate drain are monitored and indicated by the integrated self-control unit with potential free alarm contact.

### Technical data BEKOMAT 12 CO PN63

Compressor performance )*	6,5 m <sup>3</sup> /min
Refrigeration dryer performance )*	13 m <sup>3</sup> /min
Filter performance )*	65 m <sup>3</sup> /min
Operating pressure min/max.	1,2/63 bar (g)
Housing	Aluminium, hardcoated
Material membrane	FKM
Ambient temperature	+1°C/+60°C
Weight	0,9 kg
Condensate inlet	G½ [optional: NPT-Thread]
Condensate outlet (hose connection)	1 X G3/8; hose connector di = 13 mm
Electrical connection, standard	230(±10%) VAC, 50 - 60 Hz
Electrical connection, option	200,115, 100,48,24 Vac;24 Vdc
Power input	< 8,0 VA (AC/-) / W (DC/--)
Housing protection	IP 65
Cable cross section	recommended 3 X 0.75 mm <sup>2</sup>
Fuse protection	recommended AC: 1 A slow   stipulated DC: 1 A slow
Contact loading	Uac < 250 V; Iac < 0.5 A; Udc > 12 V; Idc > 50 mA

)\* Based on moderate climate (e.g. Europe)

Dimensioned Drawing BEKOMAT 12 CO PN63

